

Tech Specs

[UniFi](#) [UISP](#) [Branding](#)

[UniFi Cloud Gateways](#)

[WiFi](#)

[Switching](#)

[Cloud Keys & Gateways](#)

[Camera Security](#)

[Door Access](#)

[Phone System](#)

[New Integrations](#)

[Accessories](#)

[Accessories](#) / [UniFi Indoor Cable CMR](#)

[Datasheet](#)

[Marketing Images](#)

Mechanical

Box Dimensions	474 x 346 x 458 mm (18.7 x 13.6 x 18")
Box Weight	14.83 kg (32.69 lb)
Cable Length	305 m (1000 ft)
Cable Color	White
Cable Type	Category 6
Shielding Type	UTP
Flame Rating	CMR
Conductor Wire Gauge	23 AWG
Conductor Type	Solid Bare Copper
Jacket Material	PVC
Jacket Diameter	6.0 ± 0.2 mm
Bend Radius	Min. 24 mm
Pulling Tension	Max. 110 N
Storage Temperature	-20 to 75°C (-4 to 167°F)
Installation Temperature	0 to 60°C (32 to 140°F)
Operation Temperature	-20 to 60°C (-4 to 60°F)
Anti-Crosstalk Divider	Yes
Ripcord	Yes
Data Rate	10/100/1000 Base-T
Reference Bandwidth	Up to 600 MHz

Standards

Electrical Transmission:
ANSI/TIA-568-C.2 (2009)
ISO/IEC 11801 (Edition 2.2)
IEC 61156-5 (Edition 2.1)

Flame Test: UL 1666 (CMR)

Material and Construction:
UL 444
CSA 22.2 NO.214
EU Directive 2011/65/EU (RoHS2)
EU Directive 2006/95/EC (LVD)

Stay in Touch

 

[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2023 Ubiquiti, Inc. All rights reserved.