



[60 GHz Wireless](#)
[Wireless](#)
[Fiber](#)
[Wired](#)
[Accessory Tech](#)

[Accessory Tech](#) / [UISP Patch Cable Outdoor](#)

[Datasheet](#)

[Marketing Images](#)

Specifications

Weight	60 / 90 / 125 / 200 / 315 g (2.12 / 3.17 / 4.41 / 7.05 / 11.11 oz)
Cable length	1 / 2 / 3 / 5 / 8 m (3.28 / 6.56 / 9.84 / 16.40 / 26.25 ft)
Cable color	Black
Cable type	Category 5e
Shielding type	STP
Flame rating	VW-1 (UL1581)
Conductor wire gauge	24 AWG
Conductor type	Stranded copper
Jacket material	Thermoplastic elastomer (TPE)
Jacket diameter	6 mm (0.24")
Bend radius	Min. 24 mm (0.94")
Storage temperature	-30 to 75°C (-22 to 167°F)
Installation temperature	-20 to 60°C (-4 to 140°F)
Operation temperature	-40 to 80°C (-40 to 176°F)
Anti-crosstalk divider	No
Standards	TIA/EIA-568-B.2 ISC/IEC 11801

Stay in Touch



[Terms and Conditions](#) |
 [Terms of Service](#) |
 [Privacy Policy](#) |
 [Return Policy](#) |
 [Cookies Settings](#)

© 2023 Ubiquiti, Inc. All rights reserved.