

Tech Specs

[UniFi](#) [UISP](#) [Branding](#)

[WiFi](#) [Switching](#) [Cloud Keys & Gateways](#) [Camera Security](#) [Door Access](#) [Phone System](#) [New Int](#)

G4 Doorbell Professional PoE-to-USB Cable

[Datasheet](#)

[Marketing Images](#)

Mechanical

| | |
|------------------------------|-------------------------------|
| Weight | 326 g (11.5 oz) |
| Cable length | 7 m (22.96 ft) |
| Cable color | White |
| Shielding type | Shielded twisted pair (STP) |
| Conductor wire gauge | (2) 19 AWG + (3) 30 AWG |
| Conductor type | Stranded copper |
| Jacket material | Thermoplastic elastomer (TPE) |
| Jacket diameter | 4.8 mm (0.19 in) |
| Bend radius | Min. 19.2 mm (0.76 in) |
| Anti-crostalk divider | No |
| Flam rating | VW-1 (UL1581) |
| Storage temperature | -40 to 85° C (-40 to 185° F) |
| Operating temperature | -20 to 60° C (-4 to 140° F) |



Stay in Touch



[Terms and Conditions](#) | [Terms of Service](#) | [Privacy Policy](#) | [Return Policy](#) | [Cookies Settings](#)

© 2023 Ubiquiti, Inc. All rights reserved.