



		XR90	XR80
TECHNOLOGY SUPPORTED		5G, LTE CAT 20, LPWA	5G, LTE CAT 20, LPWA
MAX CELLULAR SPEED (DL/UL MBPS)		5G – Up to 4.14 Gbps DL/660 Mbps UL 4G LTE CAT 20 – Up to 2 Gbps DL/210 Mbps UL	5G – Up to 4.14 Gbps DL/660 Mbps UL 4G LTE CAT 20 – Up to 2 Gbps DL/210 Mbps UL
APPROVED CARRIERS*		BT, Verizon, AT&T/FirstNet and T-Mobile	BT, Verizon, AT&T/FirstNet and T-Mobile
NAVIGATION		48 Channel Dedicated Assisted GNSS with Inertial Dead Reckoning	48 Channel Dedicated Assisted GNSS with Inertial Dead Reckoning
HOST INTERFACE		Single 5G - 4 RJ-45 Ethernet ports (1x5 Gbps, 3x1 Gbps) Dual 5G - 5 RJ-45 Ethernet ports (1x5 Gbps, 4x1 Gbps) 2 USB 3.2 type-C port 1 RS-232 serial port (RJ-45 connector) 1 Aux Port (GPIO/CAN)	Single 5G - 3 RJ-45 Ethernet ports (1x5 Gbps with PTP IEEE 1588, 2x1 Gbps) Dual 5G - 4 RJ-45 Ethernet ports (1x5 Gbps with PTP IEEE 1588, 4x1 Gbps) 2 USB 3.2 type-C port 1 RS-232 serial port (RJ-45 connector) 1 Aux Port (GPIO/CAN)
SIM SLOT (2FF)		2	2
WI-FI		Dual 4X4 MIMO Wi-Fi 6 802.11 b/g/n/ac/ax 4 SSIDs	Single 4x5 MIMO Wi-Fi 6 802.11 b/g/n/ac/ax 4 SSIDs
WI-FI CLIENTS/ SECURITY		128 Clients WPA2/3 Enterprise	128 Clients WPA2/3 Enterprise
SECURITY		FIPS 140-2 (compatible) Stateful firewall with port forwarding, DMZ MAC Address filtering AAA (802.1x/RADIUS) AAA: 802.1x/Radius authentication with Wi-Fi and Ethernet Secure Firmware Update	FIPS 140-2 (compatible) Stateful firewall with port forwarding, DMZ MAC Address filtering AAA (802.1x/RADIUS) AAA: 802.1x/Radius authentication with Wi-Fi and Ethernet Secure Firmware Update
VPN		Integrated with ACM VPN Server IPsec protocol with IKEv1/IKEv2 FIPS 140-2 Encryption: AES128/AES192/AES256 Hashing: SHA256/SHA384/SHA512 Key Exchange: DHGroup14/15/16/17/18/19/20/21 LAN to LAN and Host to LAN Up to 10 concurrent tunnels per link MOBIKE protocol IP compression Full/Split Tunnel Dead Peer Detection (DPD)	Integrated with ACM VPN Server IPsec protocol with IKEv1/IKEv2 FIPS 140-2 Encryption: AES128/AES192/AES256 Hashing: SHA256/SHA384/SHA512 Key Exchange: DHGroup14/15/16/17/18/19/20/21 LAN to LAN and Host to LAN Up to 10 concurrent tunnels per link MOBIKE protocol IP compression Full/Split Tunnel Dead Peer Detection (DPD)
INDUSTRY STANDARD	Environmental	MIL-810G/IP64	MIL-810G/IP64
	Vehicle / Rail Usage, Industrial	Safety: IECCE Certification Bodies Scheme (CB Scheme), UL 60950 Vehicle Usage: E-Mark (72/245/EEC, 2009/19/EC), ISO7637-2, SAE J1455 (Shock & Vibration) Environmental: RoHS2, REACH, WEEE Rail Usage: EN50155 (Rolling Stock) Industrial: C1D2	Safety: IECCE Certification Bodies Scheme (CB Scheme), UL 60950 Vehicle Usage: E-Mark (72/245/EEC, 2009/19/EC), ISO7637-2, SAE J1455 (Shock & Vibration) Environmental: RoHS2, REACH, WEEE Rail Usage: EN50155 (Rolling Stock) Industrial: C1D2
AIRLINK MOBILITY MANAGER		No	No
AIRLINK MANAGEMENT SERVICE		Yes	Yes
CUSTOMER SUPPORT		AirLink Premium	AirLink Complete
OPERATIONAL VOLTAGE		7-36VDC	7-36VDC
OPERATING TEMPERATURE		-30°C to +70°C	-30°C to +70°C
ENCLOSURE		Die-cast aluminium	Die-cast aluminium
OPTIONAL UPGRADES		Dual cellular radios	Dual cellular radios
DIMENSIONS		Dual Radio 267 mm x 186 mm x 53 mm 10.51" x 6.69" x 2.08"	170 mm x 186 mm x 53 mm 6.69" x 7.32" x 2.08"
WARRANTY		1 year standard warranty with up to 5 years extended warranty. View specifications on our website.	1 year standard warranty with up to 5 years extended warranty. View specifications on our website.
MORE INFORMATION		sierrawireless.com/xr90	sierrawireless.com/xr80



	RX55	RV55	RV50X
TECHNOLOGY SUPPORTED	LTE-A, HSPA+	LTE-A Pro, HSPA+	LTE-A, HSPA+
MAX CELLULAR SPEED (DL/UL MBPS)	300/150 Mbps	LTE-A Pro: 600/150 Mbps LTE: 150/50 Mbps	300/50 Mbps
APPROVED CARRIERS*	Verizon, AT&T/FirstNet, T-Mobile	Verizon, AT&T/FirstNet, T-Mobile, Rogers, Bell, Telus, Telstra	Verizon, AT&T, T-Mobile, Rogers, SaskTel, Telstra, Telus
NAVIGATION	30 Channel GNSS	30 Channel GNSS	30 Channel GNSS
HOST INTERFACE	1 Ethernet (10/100/1000) 2 Serial (RS232) with accessory cable 1 CAN (RS232) with accessory cable 1 USB 2.0 (micro) 1 GPIO	1 Ethernet (10/100/1000) 2 Serial (RS232) with accessory cable 1 USB 2.0 (micro) 1 GPIO	1 Ethernet (10/100/1000) 1 Serial (RS232) 1 USB 2.0 (micro) 1 GPIO
SIM SLOT (2FF)	2	2	2
WI-FI	Dual Radio, 2.4/5GHz (Optional) 802.11 b/g/n/ac 1x1 SISO 1 SSID per radio	Dual Radio, 2.4/5GHz (Optional) 802.11 b/g/n/ac 1x1 SISO 1 SSID per radio	N/A
WI-FI CLIENTS/ SECURITY	10 clients per radio WPA2/3 Personal/Enterprise	10 clients per radio WPA2 Personal/Enterprise	N/A
SECURITY	AAA: 802.1x /Radius authentication with Wi-Fi and Ethernet Firewall: Stateful firewall with port forwarding, DMZ WLAN Encryption: WPA2/3 Personal/Enterprise Secure Firmware Update	FIPS 140-2 (compatible), Port filtering, IP whitelist, AAA (LDAP, RADIUS, TACACS+) MAC Address filtering Secure Firmware Update	FIPS 140-2 (compatible), Port filtering, IP whitelist AAA (LDAP, RADIUS, TACACS+) MAC Address filtering Secure Firmware Update
VPN	Integrated with ACM VPN Server IPsec protocol with IKEv1/IKEv2 FIPS 140-2 Level 1 compliant	IPSec: IKEv1/IKEv2, Split/full tunnel, MOBIKE, OpenVPN, GRE Tunnel, Split Tunnel, VPN failover 5 concurrent tunnels Dead Peer Detection	IPSec: IKEv1/IKEv2, Split/full tunnel, MOBIKE, OpenVPN, GRE Tunnel, Split Tunnel, VPN failover 5 concurrent tunnels Dead Peer Detection
INDUSTRY STANDARD	Environmental	MIL-810G/IP64	MIL-810G/IP64
	Vehicle / Rail Usage, Industrial	E-Mark, SAE J1455, ISO7637-2, EN50155 Industrial: Class 1 Div 2, IECEx/ATEX	E-Mark, SAE J1455, ISO7637-2, EN50155 Industrial: Class 1 Div 2
AIRLINK MOBILITY MANAGER	No	Yes	Yes
AIRLINK MANAGEMENT SERVICE	Yes	Yes	Yes
CUSTOMER SUPPORT	AirLink Complete	AirLink Complete	AirLink Complete
OPERATIONAL VOLTAGE	7-36VDC	7-36VDC	7-36VDC
OPERATING TEMPERATURE	-40°C to +70°C -30°C to +70°C (Wi-Fi variant)	-40°C to +70°C -30°C to +70°C (Wi-Fi variant)	-40°C to +70°C
ENCLOSURE	Die-cast aluminium	Die-cast aluminium	Die-cast aluminium
OPTIONAL UPGRADES	Dual Wi-Fi Dual Serial (Y cable) CAN-Serial (Y cable)	Dual Wi-Fi Dual Serial (Y cable)	N/A
DIMENSIONS	119 mm x 33 mm x 85 mm 4.69" x 1.34" x 3.35"	119 mm x 85 mm x 33 mm 4.69" x 3.35" x 1.34"	119 mm x 85 mm x 34 mm 4.68" x 3.34" x 1.34"
WARRANTY	1 year standard warranty with up to 5 years extended warranty with current AirLink Complete subscription.	1 year standard warranty with up to 5 years extended warranty. View specifications on our website.	1 year standard warranty with up to 5 years extended warranty. View specifications on our website.
MORE INFORMATION	sierrawireless.com/rx55	sierrawireless.com/rv55	sierrawireless.com/rv50x

*All approvals are either granted or in progress. Call for the latest approval status.

5G



		MG90/MG90 5G	MP70
TECHNOLOGY SUPPORTED		5G, LTE-A Pro, HSPA+	LTE-A Pro, HSPA+
MAX CELLULAR SPEED (DL/UL MBPS)		5G: 2/1 Gbps LTE-A Pro: 600/150 Mbps	600/150 Mbps
APPROVED CARRIERS*		Verizon, AT&T/FirstNet, T-Mobile, Southern Linc, Rogers, Telus, Bell	Verizon, AT&T/FirstNet, T-Mobile, Southern Linc, Rogers, Telus, Bell, Telstra
NAVIGATION		48 Channel Dedicated GNSS with Inertial Dead Reckoning	48 Channel Dedicated GNSS with Inertial Dead Reckoning
HOST INTERFACE		5 Ethernet (10/100/1000) 1 Serial (RS232) 2 USB 3.0 5 GPIO 1 Bluetooth	4 Ethernet (10/100/1000) 1 Serial (RS232) 1 USB 2.0 (micro) 5 GPIO 1 OBD-II/J1939 (Direct Vehicle CAN Interface)
SIM SLOT (2FF)		4	2
WI-FI		Dual Radio 2.4/5GHz 802.11 b/g/n/ac 3x3 MIMO 4 SSIDs	2.4/5GHz (Optional) 802.11b/g/n/ac 3x3 MIMO 4 SSIDs
WI-FI CLIENTS/ SECURITY		128 clients WPA2-Personal/Enterprise	128 clients WPA2-Personal/Enterprise
SECURITY		FIPS 140-2 (compatible), Port filtering AAA (802.1x/RADIUS) MAC Address filtering	FIPS 140-2 (compatible), Port filtering, IP whitelist, AAA (LDAP, RADIUS, TACACS+) MAC Address filtering Secure Firmware Update
VPN		IPSec: IKEv1/IKEv2 Split/full tunnel, MOBIKE 10 concurrent tunnels Dead Peer Detection	IPSec: IKEv1/IKEv2, Split/full tunnel, MOBIKE, OpenVPN, GRE Tunnel, Split Tunnel, VPN failover 5 concurrent tunnels Dead Peer Detection
INDUSTRY STANDARD	Environment	MIL-810G/IP64	MIL-810G/IP64
	Vehicle / Rail Usage, Industrial	E-Mark, SAE J1455, ISO7637-2, EN50155	E-Mark, SAE J1455, ISO7637-2, EN50155 Industrial: Class 1 Div 2
AIRLINK MOBILITY MANAGER		Yes	Yes
AIRLINK MANAGEMENT SERVICE		No	Yes
CUSTOMER SUPPORT		AirLink Support	AirLink Complete
OPERATIONAL VOLTAGE		7-36VDC	7-36VDC
OPERATING TEMPERATURE		-30°C to +70°C	-30°C to +70°C
ENCLOSURE		Die-cast aluminium	Die-cast aluminium
OPTIONAL UPGRADES		OBD-II/J1939/1708 (with Scanner Kit)	Wi-Fi OBD-II/J1939 Direct Vehicle Bus Cable
DIMENSIONS		272 mm x 220 mm x 60 mm 10.71" x 8.66" x 2.36"	190 mm x 105 mm x 45 mm 7.48" x 4.13" x 1.77"
WARRANTY		1 year standard warranty with up to 5 years extended warranty. View specifications on our website.	1 year standard warranty with up to 5 years extended warranty. View specifications on our website.
MORE INFORMATION		sierrawireless.com/mg90	sierrawireless.com/mp70

*All approvals are either granted or in progress. Call for the latest approval status.



LX40		LX60
TECHNOLOGY SUPPORTED		LTE, HSPA+
MAX CELLULAR SPEED (DL/UL MBPS)		LTE: 150/50
APPROVED CARRIERS*		Verizon, AT&T/FirstNet
NAVIGATION		N/A
HOST INTERFACE		2 Ethernet (10/100/1000) 1 Serial (RS232/485) 1 USB 2.0 (micro) 5 GPIO
SIM SLOT (2FF)		1
WI-FI		2.4/5GHz (Optional) 802.11b/g/n/ac 1x1 SISO 1 SSID
WI-FI CLIENTS/ SECURITY		10 clients WPA2 Personal/ Enterprise
SECURITY		FIPS 140-2 (compatible), Port filtering, IP whitelist AAA (LDAP, RADIUS, TACACS+) MAC Address filtering Secure Firmware Update
VPN		IPSec: IKEv1/IKEv2, Split/full tunnel, MOBIKE, OpenVPN, GRE Tunnel, Split Tunnel, VPN failover 5 concurrent tunnels Dead Peer Detection
INDUSTRY STANDARD	Environment	MIL-810G/IP21
	Vehicle / Rail Usage, Industrial	E-Mark, SAE J1455, ISO7637-3 Industrial: Class 1 Div 2
AIRLINK MOBILITY MANAGER		Yes
AIRLINK MANAGEMENT SERVICE		Yes
CUSTOMER SUPPORT		AirLink Complete
OPERATIONAL VOLTAGE		7-36VDC, PoE - Powered Device
OPERATING TEMPERATURE		-30°C to +65°C
ENCLOSURE		Polycarbonate
OPTIONAL UPGRADES		Wi-Fi
DIMENSIONS		103 mm x 79 mm x 25 mm 4.1" x 3.1" x 1.0"
WARRANTY		1 year standard warranty with up to 5 years extended warranty. View specifications on our website.
MORE INFORMATION		sierrawireless.com/lx40

*All approvals are either granted or in progress. Call for the latest approval status.

The Westbase.io team of Sierra Wireless experts is always on hand to help you. Please contact us at: +44 (0) 1291 437 567, +31 (0) 35 799 2290 or hello@westbase.io